



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We make Indiana a cleaner, healthier place to live.

Joseph E. Kernan
Governor

Lori F. Kaplan
Commissioner

February 2, 2004

100 North Senate Avenue
P.O. Box 6015
Indianapolis, Indiana 46206-6015
(317) 232-8603
(800) 451-6027
www.in.gov/idem

TO: Interested Parties / Applicant

RE: J & D Plating, LLC / MSOP 095-11713-00110

FROM: Paul Dubenetzky
Chief, Permits Branch
Office of Air Quality

Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-15-5-3, this permit is effective immediately, unless a petition for stay of effectiveness is filed and granted according to IC 13-15-6-3, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3 and IC 13-15-6-1 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, 100 North Senate Avenue, Government Center North, Room 1049, Indianapolis, IN 46204, **within eighteen (18) calendar days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) The date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for considerations at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosures
FNPER.dot 9/16/03



INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We make Indiana a cleaner, healthier place to live.

Joseph E. Kernan

Governor

Lori F. Kaplan

Commissioner

100 North Senate Avenue

P. O. Box 6015

Indianapolis, Indiana 46206-6015

(317) 232-8603

(800) 451-6027

www.IN.gov/idem

**MINOR SOURCE OPERATING PERMIT
OFFICE OF AIR QUALITY
and the
Anderson Office of Air Management**

**J & D Plating, LLC
2740 South P Street
Elwood, Indiana 46036**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this permit.

This permit is issued to the above mentioned company under the provisions of 326 IAC 2-1.1, 326 IAC 2-6.1 and 40 CFR 52.780, with conditions listed on the attached pages.

Operation Permit No.: MSOP 095-11713-00110	
Issued by:Original signed by Paul Dubenetzky Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date:February 2, 2004 Expiration Date:February 2, 2009

TABLE OF CONTENTS

A	SOURCE SUMMARY	4
A.1	General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]	
A.2	Emissions Units and Pollution Control Equipment Summary	
B	GENERAL CONDITIONS	5
B.1	Permit No Defense [IC 13]	
B.2	Definitions	
B.3	Effective Date of the Permit [IC 13-15-5-3]	
B.4	Permit Term and Renewal [326 IAC 2-6.1-7(a)] [326 IAC 2-1.1-9.5]	
B.5	Modification to Permit [326 IAC 2]	
B.6	Annual Notification [326 IAC 2-6-.1-5(a)(5)]	
B.7	Preventive Maintenance Plan [326 IAC 1-6-3]	
B.8	Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]	
B.9	Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)] [IC 13-14-2-2] [IC 13-20-3-1] [IC 13-17-3-2]	
B.10	Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]	
B.11	Annual Fee Payment [326 IAC 2-1.1-7]	
C	SOURCE OPERATION CONDITIONS	9
C.1	Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52, Subpart P] [326 IAC 6-3-2]	
C.2	Permit Revocation [326 IAC 2-1.1-9]	
C.3	Opacity [326 IAC 5-1]	
C.4	Fugitive Dust Emissions [326 IAC 6-4] [326 IAC 6-1-11.1]	
C.5	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]	
	Testing Requirements	
C.6	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.7	Compliance Requirements [326 IAC 2-1.1-11]	
	Compliance Monitoring Requirements	
C.8	Compliance Monitoring [326 IAC 2-1.1-11]	
C.9	Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]	
C.10	Compliance Response Plan - Preparation and Implementation	
C.11	Actions Related to Noncompliance Demonstrated by a Stack Test	
	Record Keeping and Reporting Requirements	
C.12	Malfunctions Report [326 IAC 1-6-2]	
C.13	General Record Keeping Requirements [326 IAC 2-6.1-5]	
C.14	General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]	
D.1	FACILITY OPERATION CONDITIONS: Combustion	15
	Emission Limitations and Standards	
D.1.1	Particulate [326 IAC 6-2-3]	

D.2 FACILITY OPERATION CONDITIONS: Electroplating line 16

Emission Limitations and Standards [326 IAC 2-6.1-5(1)]

- D.2.1 General Provisions Relating to HAPs [326 IAC 20-1-1][40 CFR Part 63, Subpart A]
- D.2.2 Chromium Electroplating and Anodizing NESHAP [326 IAC 20-8-1] [40 CFR Part 63, Subpart N]
- D.2.3 Chromium Emissions Limitation [40 CFR 63.342(c)] [40 CFR 63.343(a)(1)&(2)] [326 IAC 20-8-1]
- D.2.4 Work Practice Standards [40 CFR 63.342(f)] [326 IAC 20-8-1]
- D.2.5 Preventive Maintenance Plan [326 IAC 1-6-3]
- D.2.6 Operation and Maintenance Plan [40 CFR 63.342(f)(3)] [326 IAC 20-8-1]

Compliance Determination Requirements [326 IAC 2-1.1-11]

- D.2.7 Performance Testing Requirements [326 IAC 2-1.1-11] [40 CFR 63.343(b)(2)] [40 CFR 63.7] [40 CFR 63.344] [326 IAC 20-8-1]

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

- D.2.8 Monitoring to Demonstrate Continuous Compliance [326 IAC 2-6.1-5(a)(2)] [40 CFR 63.343(c)] [326 IAC 20-8-1]

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

- D.2.9 Record Keeping Requirements [40 CFR 63.346] [326 IAC 20-8-1]
- D.2.10 Reporting Requirements [326 IAC 3-6-4(b)] [40 CFR 63.344(a)] [40 CFR 63.345] [40 CFR 63.347] [326 IAC 20-8-1]

Ongoing Compliance Status Report	23
Malfunction Report	25
Annual Notification	27

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) and the Anderson Office of Air Management. The information describing the source contained in Conditions A.1 and A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-5.1-3(c)] [326 IAC 2-6.1-4(a)]

The Permittee owns and operates a stationary decorative chromium electroplating source.

Authorized Individual:	General Manager
Source Address:	2740 South P Street, Elwood, Indiana 46036
Mailing Address:	2740 South P Street, Elwood, Indiana 46036
General Source Phone:	(765) 552-9392
SIC Code:	3471
County Location:	Madison County
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Minor Source Operating Permit Minor Source, under PSD Rules; Minor Source, Section 112 of the Clean Air Act

A.2 Emissions Units and Pollution Control Equipment Summary

This stationary source is approved to operate the following emissions units and pollution control devices:

- (a) One (1) natural gas-fired boiler, identified as B-1, constructed in August 1983, rated at 2.0 million British thermal units per hour.
- (b) One (1) natural gas-fired space heater, identified as H-1, constructed in 1983, rated at 0.1 million British thermal units per hour.
- (c) One (1) electroplating line, with a capacity of 256 pounds of steel wire per hour, including:
 - (1) one (1) decorative chromium electroplating tank, identified as DC-1, constructed in 1983, using a fume suppressant containing a wetting agent to control emissions;
 - (2) one (1) nickel electroplating tank;
 - (3) two (2) acid cleaner tanks, using sulfuric and hydrochloric acids;
 - (4) two (2) caustic cleaner tanks, using only non-VOC materials; and
 - (5) rinse tanks.

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1.1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

This permit to operate does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations IC 13-11, 326 IAC 1-2, and 326 IAC 2-1.1-1 shall prevail.

Pursuant to IC 13-15-5-3, this permit becomes effective upon its issuance.

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions of this permit do not affect the expiration date.

The Permittee shall apply for an operation permit renewal at least ninety (90) days prior to the expiration date. If a timely and sufficient permit application for a renewal has been made, this permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

All requirements and conditions of this operating permit shall remain in effect unless modified in a manner consistent with procedures established for modifications of construction permits pursuant to 326 IAC 2 (Permit Review Rules).

(a) Annual notification shall be submitted to the Office of Air Quality stating whether or not the source is in operation and in compliance with the terms and conditions contained in this permit.

- (b) Noncompliance with any condition must be specifically identified. If there are any permit conditions or requirements for which the source is not in compliance at any time during the year, the Permittee must provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be, achieved. The notification must be signed by an authorized individual.
- (c) The annual notice shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in the format attached no later than March 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

and

Anderson Office of Air Management
P.O. Box 2100
120 East 8th Street
Anderson, IN 46011

- (d) The notification shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and the Anderson Office of Air Management on or before the date it is due.

B.7 Preventive Maintenance Plan [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each emissions unit:

- (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
- (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
- (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management
P.O. Box 2100
120 East 8th Street
Anderson, IN 46011

The PMP extension notification does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall implement the PMPs, including any required record keeping, as necessary to ensure that failure to implement a PMP does not cause or contribute to an exceedance of any limitation on emissions or potential to emit.
- (c) A copy of the PMP's shall be submitted to IDEM, OAQ, and the Anderson Office of Air Management upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ, and the Anderson Office of Air Management. IDEM, OAQ, and the Anderson Office of Air Management may require the Permittee to revise its PMP whenever

lack of proper maintenance causes or is the primary contributor to an exceedance of any limitation on emissions or potential to emit. The PMP does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (d) To the extent the Permittee is required by 40 CFR Part 60/63 to have an Operation, Maintenance, and Monitoring (OMM) Plan for a unit, such Plan is deemed to satisfy the PMP requirements of 326 IAC 1-6-3 for that unit.

B.8 Permit Revision [326 IAC 2-5.1-3(e)(3)] [326 IAC 2-6.1-6]

- (a) Permit revisions are governed by the requirements of 326 IAC 2-6.1-6.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management
P.O. Box 2100
120 East 8th Street
Anderson, IN 46011

Any such application shall be certified by an "authorized individual" as defined by 326 IAC 2-1.1-1.
- (c) The Permittee shall notify the OAQ within thirty (30) calendar days of implementing a notice-only change. [326 IAC 2-6.1-6(d)]
- (d) No permit amendment or modification is required for the addition, operation or removal of a nonroad engine, as defined in 40 CFR 89.2.

B.9 Inspection and Entry [326 IAC 2-5.1-3(e)(4)(B)] [326 IAC 2-6.1-5(a)(4)] [IC 13-14-2-2] [IC 13-20-3-1] [IC 13-17-3-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, the Anderson Office of Air Management, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a permitted source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, have access to and copy, at reasonable times, any records that must be kept under this title or the conditions of this permit or any operating permit revisions;
- (c) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, inspect, at reasonable times, any processes, emissions units (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit or any

operating permit revisions;

- (d) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) As authorized by the Clean Air Act, IC 13-14-2-2, IC 13-17-3-2, and IC 13-30-3-1, utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.10 Transfer of Ownership or Operation [326 IAC 2-6.1-6(d)(3)]

Pursuant to [326 IAC 2-6.1-6(d)(3)] :

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAQ, Permits Branch, and the Anderson Office of Air Management within thirty (30) days of the change.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an notice-only change pursuant to 326 IAC 2-6.1-6(d)(3).
- (c) IDEM, OAQ, and the Anderson Office of Air Management shall issue a revised permit.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

B.11 Annual Fee Payment [326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing.
- (b) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

C.1 Particulate Emission Limitation For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(e)(2), particulate emissions from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour.

C.2 Permit Revocation [326 IAC 2-1.1-9]

Pursuant to 326 IAC 2-1.1-9 (Revocation of Permits), this permit to operate may be revoked for any of the following causes:

- (a) Violation of any conditions of this permit.
- (b) Failure to disclose all the relevant facts, or misrepresentation in obtaining this permit.
- (c) Changes in regulatory requirements that mandate either a temporary or permanent reduction of discharge of contaminants. However, the amendment of appropriate sections of this permit shall not require revocation of this permit.
- (d) Noncompliance with orders issued pursuant to 326 IAC 1-5 (Episode Alert Levels) to reduce emissions during an air pollution episode.
- (e) For any cause which establishes in the judgment of IDEM and the Anderson Office of Air Management, the fact that continuance of this permit is not consistent with purposes of this article.

C.3 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.4 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.5 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35)

cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management
P.O. Box 2100
120 East 8th Street
Anderson, IN 46011

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by an "authorized individual" as defined by 326 IAC 2-7-1(34).

- (e) Procedures for Asbestos Emission Control
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) Demolition and renovation
The Permittee shall thoroughly inspect the affected facility or part of the facility where the

demolition or renovation will occur for the presence of asbestos pursuant to 40 CFR 61.145(a).

- (g) Indiana Accredited Asbestos Inspector
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement to use an Indiana Accredited Asbestos inspector is not federally enforceable.

Testing Requirements

C.6 Performance Testing [326 IAC 3-6]

- (a) Compliance testing on new emissions units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management
P.O. Box 2100
120 East 8th Street
Anderson, IN 46011

no later than thirty-five (35) days prior to the intended test date.

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual date.
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ, and the Anderson Office of Air Management not later than forty-five (45) days after the completion of the testing. An extension may be granted by the IDEM, OAQ, and the Anderson Office of Air Management, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.7 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U.S. EPA.

Compliance Monitoring Requirements

C.8 Compliance Monitoring [326 IAC 2-1.1-11]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. All monitoring and record keeping requirements not already legally required shall be implemented when operation begins.

C.9 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60, Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

C.10 Compliance Response Plan - Preparation and Implementation

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. The Operation and Maintenance Plan (OMP) required by Condition D.1.6 shall satisfy the requirements for a CRP for those compliance monitoring conditions. A CRP shall be submitted to IDEM, OAQ, and the Anderson Office of Air Management upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected time frame for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan or Operation and Maintenance Plan (OMP), the Permittee shall amend its Compliance Response Plan or Operation and Maintenance Plan (OMP) to include such response steps taken.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, and it will be 10 days or more until the unit or device will be shut down, then the permittee shall promptly notify the IDEM, OAQ of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan or Operation and Maintenance Plan (OMP); or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan or Operation and Maintenance Plan (OMP) is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, and it will be 10 days or more until the unit or device will be shut down, then the permittee shall promptly notify the IDEM, OAQ of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall be considered a deviation from the permit.

- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.11 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected emissions unit while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The response action documents submitted pursuant to this condition do not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1.

Record Keeping and Reporting Requirements

C.12 Malfunctions Report [326 IAC 1-6-2]

Pursuant to 326 IAC 1-6-2 (Records; Notice of Malfunction):

- (a) A record of all malfunctions, including startups or shutdowns of any facility or emission control equipment, which result in violations of applicable air pollution control regulations or applicable emission limitations shall be kept and retained for a period of three (3) years and shall be made available to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) or appointed representative upon request.
- (b) When a malfunction of any facility or emission control equipment occurs which lasts more than one (1) hour, said condition shall be reported to OAQ, using the Malfunction Report

Forms (2 pages). Notification shall be made by telephone or facsimile, as soon as practicable, but in no event later than four (4) daytime business hours after the beginning of said occurrence.

- (c) Failure to report a malfunction of any emission control equipment shall constitute a violation of 326 IAC 1-6, and any other applicable rules. Information of the scope and expected duration of the malfunction shall be provided, including the items specified in 326 IAC 1-6-2(a)(1) through (6).
- (d) Malfunction is defined as any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner. [326 IAC 1-2-39]

C.13 General Record Keeping Requirements [326 IAC 2-6.1-5]

- (a) Records of all required monitoring data, reports and support information required by this permit shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be physically present or electronically accessible at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner or the Anderson Office of Air Management makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner or the Anderson Office of Air Management within a reasonable time.
- (b) Unless otherwise specified in this permit, all record Keeping requirements not already legally required shall be implemented when operation begins.

C.14 General Reporting Requirements [326 IAC 2-1.1-11] [326 IAC 2-6.1-2] [IC 13-14-1-13]

- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

Anderson Office of Air Management
P.O. Box 2100
120 East 8th Street
Anderson, IN 46011

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, and the Anderson Office of Air Management on or before the date it is due.
- (c) Unless otherwise specified in this permit, any semi-annual report required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by an "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (d) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description: Combustion

- (a) One (1) natural gas-fired boiler, identified as B-1, constructed in August 1983, rated at 2.0 million British thermal units per hour.
- (b) One (1) natural gas-fired space heater, identified as H-1, constructed in 1983, rated at 0.1 million British thermal units per hour.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards

D.1.1 Particulate [326 IAC 6-2-3]

- (a) Pursuant to 326 IAC 6-2-3 (Particulate Emission Limitations for Sources of Indirect Heating) the PM emissions from the 2.0 million British thermal units per hour heat input boiler shall be limited to 0.6 pounds per million British thermal units heat input.
- (b) Pursuant to 326 IAC 6-2-3(e), for total heat input capacities less than 10 million British thermal units per hour, the PM emissions shall not exceed 0.6 pounds per million British thermal units heat input.

SECTION D.2

FACILITY OPERATION CONDITIONS

Facility Description:

- (c) One (1) electroplating line, with a capacity of 256 pounds of steel wire per hour, including:
- (1) one (1) decorative chromium electroplating tank, identified as DC-1, constructed in 1983, using a fume suppressant containing a wetting agent to control emissions;
 - (2) one (1) nickel electroplating tank;
 - (3) two (2) acid cleaner tanks, using sulfuric and hydrochloric acids;
 - (4) two (2) caustic cleaner tanks, using only non-VOC materials; and
 - (5) rinse tanks.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-6.1-5(1)]

D.2.1 General Provisions Relating to HAPs [326 IAC 20-1-1][40 CFR Part 63, Subpart A]

The provisions of 40 CFR Part 63, Subpart A - General Provisions, which are incorporated by reference as 326 IAC 20-1-1, apply to the decorative chromium electroplating tank (DC-1) described in this section except when otherwise specified in 40 CFR Part 63, Subpart N.

D.2.2 Chromium Electroplating and Anodizing NESHAP [326 IAC 20-8-1] [40 CFR Part 63, Subpart N]

The provisions of 40 CFR 63, Subpart N - National Emission Standards for Chromium Emissions From Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks, which are incorporated by reference as 326 IAC 20-8-1, apply to tank DC-1. A copy of this rule is attached.

D.2.3 Chromium Emissions Limitation [40 CFR 63.342(c)] [40 CFR 63.343(a)(1)&(2)] [326 IAC 20-8-1]

- (a) The emission limitations in this condition apply only during tank operation, and also apply during periods of startup and shutdown as these are routine occurrences for tanks subject to 326 IAC 20-8-1. The emission limitations do not apply during periods of malfunction.
- (b) During tank operation, the Permittee shall control chromium emissions discharged to the atmosphere from tank DC-1 by:
- (1) Not allowing the concentration of total chromium in the exhaust gas stream discharged to the atmosphere to exceed one-hundredth milligrams of total chromium per dry standard cubic meter of ventilation air (0.01 mg/dscm) [equivalent to four and four-tenths times ten raised to the power of negative six grains of total chromium per dry standard cubic foot of ventilation air (4.4×10^{-6} gr/dscf)]; or
 - (2) Not allowing the surface tension of the electroplating bath contained within the tank to exceed forty-five dynes per centimeter (45 dynes/cm) [equivalent to three and one-tenth times ten raised to the power of negative three pound-force per foot (3.1×10^{-3} lb_f/ft)] at any time during operation of tank DC-1 when a chemical fume suppressant containing a wetting agent is used.

D.2.4 Work Practice Standards [40 CFR 63.342(f)] [326 IAC 20-8-1]

The following work practice standards apply to tank DC-1:

- (a) At all times, including periods of startup, shutdown, malfunction and excess emissions, the Permittee shall operate and maintain tank DC-1, including the fume suppressant containing a wetting agent, in a manner consistent with good air pollution control practices, consistent with the Operation and Maintenance Plan (OMP) required by Condition D.2.6.
- (b) Malfunctions and excess emissions shall be corrected as soon as practicable after their occurrence in accordance with the OMP required by Condition D.2.6.
- (c) These operation and maintenance requirements are enforceable independent of emissions limitations or other requirements in this section.
- (d) Determination of whether acceptable operation and maintenance procedures are being used will be based on information available to IDEM, OAQ, which may include, but is not limited to, monitoring results; review of the OMP, procedures, and records; and inspection of the source.
- (e) Based on the results of a determination made under paragraph (d) of this condition, IDEM, OAQ may require that the Permittee make changes to the OMP required by Condition D.2.6. Revisions may be required if IDEM, OAQ finds that the plan:
 - (1) Does not address a malfunction or period of excess emissions that has occurred;
 - (2) Fails to provide for the operation of tank DC-1 or the fume suppressant containing a wetting agent and process monitoring equipment during a malfunction or period of excess emissions in a manner consistent with good air pollution control practices; or
 - (3) Does not provide adequate procedures for correcting malfunctioning process equipment, the fume suppressant containing a wetting agent, monitoring equipment or other causes of excess emissions as quickly as practicable.

The work practice standards that address operation and maintenance must be followed during malfunctions and periods of excess emissions.

D.2.5 Preventive Maintenance Plan [326 IAC 1-6-3]

A Preventive Maintenance Plan (PMP), in accordance with Section B-Preventive Maintenance Plan, of this permit, is required for tank DC-1.

D.2.6 Operation and Maintenance Plan [40 CFR 63.342(f)(3)] [326 IAC 20-8-1]

- (a) The Permittee shall prepare an Operation and Maintenance Plan (OMP) to be implemented no later than the startup date of tank DC-1. The OMP shall specify the operation and maintenance criteria for tank DC-1, the fume suppressant containing a wetting agent and monitoring equipment and shall include the following elements:
 - (1) Manufacturers recommendations for maintenance of the monitoring equipment used to measure surface tension;
 - (2) A standardized checklist to document the operation and maintenance criteria for tank DC-1, the fume suppressant containing a wetting agent and the monitoring equipment.

- (3) Procedures to be followed to ensure that equipment or process malfunctions due to poor maintenance or other preventable conditions or periods of excess emissions as indicated by monitoring data do not occur.
- (4) A systematic procedure for identifying malfunctions and periods of excess emissions of tank DC-1, the fume suppressant containing a wetting agent and monitoring equipment; and for implementing corrective actions to address such malfunctions and periods of excess emissions.
- (b) The Permittee may use applicable standard operating procedures (SOP) manuals, Occupational Safety and Health Administration (OSHA) plans, or other existing plans such as the PMP required in Condition D.2.5, as the OMP, provided the alternative plans meet the above listed criteria in Condition D.2.6(a).
- (c) If the OMP fails to address or inadequately addresses an event that meets the characteristics of a malfunction or period of excess emissions at the time the plan is initially developed, the Permittee shall revise the OMP within forty-five (45) days after such an event occurs. The revised plan shall include procedures for operating and maintaining tank DC-1, the fume suppressant containing a wetting agent and the monitoring equipment, during similar malfunction or period of excess emissions events, and a program for corrective action for such events.
- (d) If actions taken by the Permittee during periods of malfunction or period of excess emissions are inconsistent with the procedures specified in the OMP, the Permittee shall record the actions taken for that event and shall report by phone such actions within two (2) working days after commencing actions inconsistent with the plan. This report shall be followed by a letter within seven (7) working days after the end of the event, unless the Permittee makes alternative reporting arrangements, in advance, with IDEM, OAQ.
- (e) The Permittee shall keep the written OMP on record after it is developed to be made available, upon request, by IDEM, OAQ for the life of tank DC-1 or until the tank is no longer subject to the provisions of 40 CFR 63.340. In addition, if the OMP is revised, the Permittee shall keep previous versions of the OMPs on record to be made available for inspection, upon request by IDEM, OAQ for a period of five (5) years after each revision to the plan.

Compliance Determination Requirements [326 IAC 2-1.1-11]

D.2.7 Performance Testing [326 IAC 2-1.1-11] [40 CFR 63.343(b)(2)] [40 CFR 63.7] [40 CFR 63.344] [326 IAC 20-8-1]

-
- (a) Pursuant to 40 CFR 63.343(c)(5)(i), the Permittee has accepted 45 dynes/cm as the maximum surface tension value that corresponds to compliance with the applicable emission limitation, 0.01 mg/dscm (4.4×10^{-6} gr/dscf), in lieu of establishing the maximum surface tension during an initial performance test. The Permittee is exempt from conducting a performance test only if the criteria of 40 CFR 63.343(b)(2) are met.
 - (b) The Permittee is not required to test DC-1 by this permit. However, the IDEM may require testing when necessary to determine if the tank is in compliance. If testing is required by the IDEM, compliance with the limit specified in Condition D.2.3 shall be determined by a performance test conducted in accordance with 40 CFR 63.344 and Section C - Performance Testing.
 - (c) Any change, modification, or reconstruction of tank DC-1, the fume suppressant containing

a wetting agent or monitoring equipment may require additional performance testing conducted in accordance with 40 CFR 63.344 and Section C - Performance Testing.

Compliance Monitoring Requirements [326 IAC 2-6.1-5(a)(2)]

D.2.8 Monitoring to Demonstrate Continuous Compliance [326 IAC 2-6.1-5(a)(2)] [40 CFR 63.343(c)] [326 IAC 20-8-1]

-
- (a) Pursuant to 40 CFR 63.343(c)(5)(ii) and (iii), when using a wetting agent in the electroplating bath to comply with the limit specified in Condition D.2.3, the Permittee shall monitor the surface tension of the electroplating baths. Operation of tank DC-1 at a surface tension greater than 45 dynes per centimeter shall constitute noncompliance with the standards.
- (1) The Permittee shall monitor the surface tension of the electroplating bath during tank operation according to the following schedule:
- (A) The surface tension shall be measured once every 4 hours during operation of the tank with a stalagmometer or a tensiometer as specified in Method 306B, appendix A of this part.
- (B) The time between monitoring can be increased if there have been no exceedances. The surface tension shall be measured once every 4 hours of tank operation for the first 40 hours of tank operation after the compliance date. Once there are no exceedances during 40 hours of tank operation, surface tension measurement may be conducted once every 8 hours of tank operation. Once there are no exceedances during 40 hours of tank operation, surface tension measurement may be conducted once every 40 hours of tank operation on an ongoing basis, until an exceedance occurs. The minimum frequency of monitoring allowed by this subpart is once every 40 hours of tank operation.
- (C) Once an exceedance occurs as indicated through surface tension monitoring, the original monitoring schedule of once every 4 hours must be resumed. A subsequent decrease in frequency shall follow the schedule laid out in paragraph (B) above. For example, if a Permittee had been monitoring a tank once every 40 hours and an exceedance occurs, subsequent monitoring would take place once every 4 hours of tank operation. Once an exceedance does not occur for 40 hours of tank operation, monitoring can occur once every 8 hours of tank operation. Once an exceedance does not occur for 40 hours of tank operation on this schedule, monitoring can occur once every 40 hours of tank operation.
- (2) Once a bath solution is drained from tank DC-1 and a new solution added, the original monitoring schedule of once every 4 hours must be resumed, with a decrease in monitoring frequency allowed following the procedures in paragraphs (B) and (C) above.
- (b) Tank operation or operating time is defined as that time when a part is in the tank and there is a current running through the tank. If the amount of time that no part is in the tank is fifteen minutes or longer, that time is not considered operating time. Likewise, if the amount of time between placing parts in the tank (i.e., when no part is in the tank) is less than fifteen minutes, that time between plating the two parts may be considered operating time.

Record Keeping and Reporting Requirements [326 IAC 2-6.1-5(a)(2)]

D.2.9 Record Keeping Requirements [40 CFR 63.346] [326 IAC 20-8-1]

The Permittee shall maintain records to document compliance with Conditions D.2.3, D.2.4 and D.2.6 using the forms provided with this permit. These records shall be maintained in accordance with Section C - General Record Keeping Requirements of this permit and include a minimum of the following:

- (a) Inspection records for the fume suppressant containing a wetting agent and monitoring equipment to document that the inspection and maintenance required by Conditions D.2.8 have taken place. The record can take the form of a checklist and should identify the following:
 - (1) The device inspected;
 - (2) The date of inspection;
 - (3) A brief description of the working condition of the device during the inspection, including any deficiencies found; and
 - (4) Any actions taken to correct deficiencies found during the inspection, including the date(s) such actions were taken.
- (b) Records of all maintenance performed on tank DC-1 and monitoring equipment.
- (c) Records of the occurrence, duration, and cause (if known) of each malfunction of tank DC-1 and monitoring equipment.
- (d) Records of the occurrence, duration, and cause (if known) of each period of excess emissions of tank DC-1 and monitoring equipment as indicated by monitoring data collected in accordance with this condition.
- (e) Records of actions taken during periods of malfunction or excess emissions when such actions are inconsistent with the OMP.
- (f) Other records, which may take the form of checklists, necessary to demonstrate consistency with the provisions of the OMP.
- (g) Test reports documenting results of all performance tests.
- (h) All measurements as may be necessary to determine the conditions of performance tests, including measurements necessary to determine compliance.
- (i) Records of monitoring data required by 40 CFR 63.343(c) that are used to demonstrate compliance with the standard including the date and time the data are collected.
- (j) The total process operating time, as defined in Condition D.2.8(b), of each tank, during the reporting period.
- (k) Records of the date and time that fume suppressants were added to the electroplating bath, and the amount and type of fume suppressants added.
- (l) All documentation supporting the notifications and reports required by 40 CFR 63.9 and 63.10 (Subpart A, General Provisions) and by Condition D.2.10.

D.2.10 Reporting Requirements [326 IAC 3-6-4(b)] [40 CFR 63.344(a), 63.345 and 63.347] [326 IAC 20-8-1]

The notifications and reports required in this section shall be submitted to IDEM, OAQ using the address specified in Section C - General Reporting Requirements.

(a) Notifications:

(1) Initial Notifications

The Permittee shall notify IDEM, OAQ in writing that the source is subject to 40 CFR Part 63, Subpart N. The notification shall be submitted no later than one hundred eighty (180) days after the compliance date and shall contain the information listed in 40 CFR 63.347(c)(1).

(2) A Notification of Compliance Status (NCS) is required each time that the facility becomes subject to the requirements of 40 CFR Part 63 Subpart N.

(A) The NCS shall be submitted to IDEM, OAQ, and shall list, for each tank, the information identified in 40 CFR 63.347(e)(2).

(B) The NCS for tank DC-1 shall be submitted to IDEM, OAQ immediately.

(3) Notification of Construction or Reconstruction

Pursuant to 40 CFR 63.345(b)(1), the Permittee may not construct a new tank subject to 40 CFR 63, Subpart N (including non-affected tanks defined in 40 CFR 63.344(e)) without submitting a Notification of Construction or Reconstruction (NCR) to IDEM, OAQ. In addition, the Permittee may not change, modify, or reconstruct tank DC-1 without submitting a Notification of Construction or Reconstruction (NCR) to IDEM, OAQ.

(A) The NCR shall contain the information identified in 40 CFR 63.345(b) (2) and (3).

(B) A change, modification, or reconstruction of this facility includes any change in the air pollution control techniques, the addition of add-on control devices, or the construction of duct work for the purpose of controlling both existing tanks and non-affected facilities by a common control technique or device.

(C) A complete application to construct new chromium electroplating or chromium anodizing tanks serves as this notification. Likewise, the complete application to modify or reconstruct tank DC-1.

(D) serves as this notification.

(E) Pursuant to 326 IAC 2-1.1-2(a), permission must be received from IDEM, OAQ before construction, modification, or reconstruction may commence.

(b) Performance Test Results

The Permittee shall document results from any future performance tests in a complete test report that contains the information required in 40 CFR 344(a).

The Permittee shall submit reports of performance test results as part of the Notification of Compliance Status, described in 40 CFR 63.347(e), no later than forty-five (45) days following the completion of the performance test.

(c) Ongoing Compliance Status Report

The Permittee shall prepare summary reports to document the ongoing compliance status of tank DC-1 using the Ongoing Compliance Status Report form provided with this permit. This report shall contain the information specified in 40 CFR 63.347(g)(3).

Because tank DC-1 is located at site that is an area source of hazardous air pollutants (HAPs), the Ongoing Compliance Status Report shall be retained on site and made available to IDEM, OAQ upon request.

- (1) The Ongoing Compliance Status Report shall be completed according to the following schedule except as provided in paragraphs (c)(2).
 - (A) The first report shall cover the period from the issuance date of this permit to December 31 of the year in which the permit is issued.
 - (B) Following the first year of reporting, the report shall be completed on a calendar year basis with the reporting period covering from January 1 to December 31.
- (2) If both of the following conditions are met, semiannual reports shall be prepared and submitted to IDEM, OAQ:
 - (A) The total duration of excess emissions (as indicated by the monitoring data collected by the Permittee in accordance with 40 CFR 63.343(c)) is one percent (1%) or greater of the total operating time as defined in Condition D.2.8(b) for the reporting period; and
 - (B) The total duration of malfunctions of the add-on air pollution control device and monitoring equipment is five percent (5%) or greater of the total operating time as defined in Condition D.2.8(b).

Once the Permittee reports an exceedance as defined above, Ongoing Compliance Status Reports shall be submitted semiannually until a request to reduce reporting frequency in accordance with 40 CFR 63.347(g)(2) is approved.

- (3) IDEM, OAQ may determine on a case-by-case basis that the summary report shall be completed more frequently and submitted, or that the annual report shall be submitted instead of being retained on site, if these measures are necessary to accurately assess the compliance status of the source.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
CHROMIUM ELECTROPLATING AND ANODIZING NESHAP
ONGOING COMPLIANCE STATUS REPORT**

Source Name: J & D Plating, LLC
Source Address: 2740 South P Street, Elwood, Indiana 46036
Mailing Address: 2740 South P Street, Elwood, Indiana 46036
Minor Source Operating Permit No.: 095-11713-00110
Tank ID #: DC-1
Type of process: Decorative Chromium Electroplating
Monitoring Parameter: Surface tension of the electroplating bath
Parameter Value: 45 dynes per centimeter
Limits: Total chromium concentration may not exceed 0.01 mg/dscm

This form is to be used to report compliance for the Chromium Electroplating and Anodizing NESHAP only.
The frequency for completing this report may be altered by IDEM, OAQ, Compliance Branch.

Companies classified as an area source: *Complete this report no later than 30 days after the end of the reporting period, and retain on site unless otherwise notified.*

This form consists of 2 pages

Page 1 of 2

BEGINNING AND ENDING DATES OF THE REPORTING PERIOD:

TOTAL OPERATING TIME OF THE TANK DURING THE REPORTING PERIOD:

MAJOR AND AREA SOURCES: CHECK ONE

? NO DEVIATIONS OF THE MONITORING PARAMETER ASSOCIATED WITH THIS TANK FROM THE COMPLIANT VALUE OR RANGE OF VALUES OCCURRED DURING THIS REPORTING PERIOD.

? THE MONITORING PARAMETER DEVIATED FROM THE COMPLIANT VALUE OR RANGE OF VALUES DURING THIS REPORTING PERIOD (THUS INDICATING THE EMISSION LIMITATION MAY HAVE BEEN EXCEEDED, WHICH COULD RESULT IN MORE FREQUENT REPORTING).

AREA (I.E., NON-MAJOR) SOURCES OF HAP ONLY:

IF DEVIATIONS OCCURRED, LIST THE AMOUNT OF TANK OPERATING TIME EACH MONTH THAT MONITORING RECORDS SHOW THE MONITORING PARAMETER DEVIATED FROM THE COMPLIANT VALUE OR RANGE OF VALUES.

JAN	APR	JUL	OCT
FEB	MAY	AUG	NOV
MAR	JUN	SEP	DEC

HARD CHROME TANKS / MAXIMUM RECTIFIER CAPACITY LIMITED IN ACCORDANCE WITH 40 CFR 63.342(c)(2) ONLY:

LIST THE ACTUAL AMPERE-HOURS CONSUMED (BASED ON AN AMP-HR METER) BY THE INDIVIDUAL TANK.

JAN	APR	JUL	OCT
FEB	MAY	AUG	NOV
MAR	JUN	SEP	DEC

CHROMIUM ELECTROPLATING AND ANODIZING NESHAP ONGOING COMPLIANCE STATUS REPORT

ATTACH A SEPARATE PAGE IF NEEDED

Page 2 of 2

IF THE OPERATION AND MAINTENANCE PLAN REQUIRED BY 40 CFR 63.342 (f)(3) WAS NOT FOLLOWED, PROVIDE AN EXPLANATION OF THE REASONS FOR NOT FOLLOWING THE PLAN AND DESCRIBE THE ACTIONS TAKEN FOR THAT EVENT:

DESCRIBE ANY CHANGES IN TANKS, RECTIFIERS, CONTROL DEVICES, MONITORING, ETC. SINCE THE LAST STATUS REPORT:

ADDITIONAL COMMENTS:

ALL SOURCES: CHECK ONE

?

I CERTIFY THAT THE WORK PRACTICE STANDARDS IN 40 CFR 63.342(f) WERE FOLLOWED IN ACCORDANCE WITH THE OPERATION AND MAINTENANCE PLAN ON FILE; AND, THAT THE INFORMATION CONTAINED IN THIS REPORT IS ACCURATE AND TRUE TO THE BEST OF MY KNOWLEDGE.

?

THE WORK PRACTICE STANDARDS IN 40 CFR 63.342(f) WERE NOT FOLLOWED IN ACCORDANCE WITH THE OPERATION AND MAINTENANCE PLAN ON FILE, AS EXPLAINED ABOVE AND/OR ON ATTACHED.

Submitted by: _____

Title/Position: _____

Signature: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

MALFUNCTION REPORT

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
FAX NUMBER - 317 233-5967**

**This form should only be used to report malfunctions applicable to Rule 326 IAC 1-6
and to qualify for the exemption under 326 IAC 1-6-4.**

THIS FACILITY MEETS THE APPLICABILITY REQUIREMENTS BECAUSE IT HAS POTENTIAL TO EMIT 25 TONS/YEAR PARTICULATE MATTER ?____, 25 TONS/YEAR SULFUR DIOXIDE ?____, 25 TONS/YEAR NITROGEN OXIDES ?____, 25 TONS/YEAR VOC ?____, 25 TONS/YEAR HYDROGEN SULFIDE ?____, 25 TONS/YEAR TOTAL REDUCED SULFUR ?____, 25 TONS/YEAR REDUCED SULFUR COMPOUNDS ?____, 25 TONS/YEAR FLUORIDES ?____, 100 TONS/YEAR CARBON MONOXIDE ?____, 10 TONS/YEAR ANY SINGLE HAZARDOUS AIR POLLUTANT ?____, 25 TONS/YEAR ANY COMBINATION HAZARDOUS AIR POLLUTANT ?____, 1 TON/YEAR LEAD OR LEAD COMPOUNDS MEASURED AS ELEMENTAL LEAD ?____, OR IS A SOURCE LISTED UNDER 326 IAC 2-5.1-3(2) ?____. EMISSIONS FROM MALFUNCTIONING CONTROL EQUIPMENT OR PROCESS EQUIPMENT CAUSED EMISSIONS IN EXCESS OF APPLICABLE LIMITATION _____.

THIS MALFUNCTION RESULTED IN A VIOLATION OF: 326 IAC _____ OR, PERMIT CONDITION # _____ AND/OR PERMIT LIMIT OF _____

THIS INCIDENT MEETS THE DEFINITION OF 'MALFUNCTION' AS LISTED ON REVERSE SIDE ? Y N

THIS MALFUNCTION IS OR WILL BE LONGER THAN THE ONE (1) HOUR REPORTING REQUIREMENT ? Y N

COMPANY: _____ PHONE NO. : _____
LOCATION: (CITY AND COUNTY) _____
PERMIT NO. _____ AFS PLANT ID: _____ AFS POINT ID: _____ INSP: _____
CONTROL/PROCESS DEVICE WHICH MALFUNCTIONED AND REASON: _____

DATE/TIME MALFUNCTION STARTED: ____/____/20____ _____ AM / PM

ESTIMATED HOURS OF OPERATION WITH MALFUNCTION CONDITION: _____

DATE/TIME CONTROL EQUIPMENT BACK-IN SERVICE ____/____/20____ _____ AM / PM

TYPE OF POLLUTANTS EMITTED: TSP, PM₁₀, SO₂, VOC, OTHER: _____

ESTIMATED AMOUNT OF POLLUTANT EMITTED DURING MALFUNCTION: _____

MEASURES TAKEN TO MINIMIZE EMISSIONS: _____

REASONS WHY FACILITY CANNOT BE SHUTDOWN DURING REPAIRS:

CONTINUED OPERATION REQUIRED TO PROVIDE ESSENTIAL* SERVICES: _____
CONTINUED OPERATION NECESSARY TO PREVENT INJURY TO PERSONS: _____
CONTINUED OPERATION NECESSARY TO PREVENT SEVERE DAMAGE TO EQUIPMENT: _____
INTERIM CONTROL MEASURES: (IF APPLICABLE) _____

MALFUNCTION REPORTED BY: _____ TITLE: _____
(SIGNATURE IF FAXED)

MALFUNCTION RECORDED BY: _____ DATE: _____ TIME: _____

*SEE PAGE 2

PAGE 1 OF 2

**Please note - This form should only be used to report malfunctions
applicable to Rule 326 IAC 1-6 and to qualify for
the exemption under 326 IAC 1-6-4.**

326 IAC 1-6-1 Applicability of rule

Sec. 1. This rule applies to the owner or operator of any facility required to obtain a permit under 326 IAC 2-5.1 or 326 IAC 2-6.1.

326 IAC 1-2-39 "Malfunction" definition

Sec. 39. Any sudden, unavoidable failure of any air pollution control equipment, process, or combustion or process equipment to operate in a normal and usual manner.

* **Essential services** are interpreted to mean those operations, such as, the providing of electricity by power plants. Continued operation solely for the economic benefit of the owner or operator shall not be sufficient reason why a facility cannot be shutdown during a control equipment shutdown.

If this item is checked on the front, please explain rationale:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH**

**MINOR SOURCE OPERATING PERMIT
ANNUAL NOTIFICATION**

This form should be used to comply with the notification requirements under 326 IAC 2-6.1-5(a)(5).

Company Name:	J & D Plating, LLC
Address:	2740 South P Street
City:	Elwood
Phone #:	(765) 552-9392
MSOP #:	095-11713-00110

I hereby certify that J & D Plating, LLC is ☐ still in operation.
 ☐ no longer in operation.

I hereby certify that J & D Plating, LLC is ☐ in compliance with the requirements of MSOP **095-11713-00110**.
 ☐ not in compliance with the requirements of MSOP **095-11713-00110**.

Authorized Individual (typed):
Title:
Signature:
Date:

If there are any conditions or requirements for which the source is not in compliance, provide a narrative description of how the source did or will achieve compliance and the date compliance was, or will be achieved.

Noncompliance:

**Indiana Department of Environmental Management
Office of Air Quality
and the
Anderson Office of Air Management**

**Technical Support Document (TSD) for
a Minor Source Operating Permit**

Source Background and Description

Source Name:	J & D Plating, LLC
Source Location:	2740 South P Street, Elwood, Indiana 46036
County:	Madison
SIC Code:	3471
Operation Permit No.:	MSOP 095-11713-00110
Permit Reviewer:	CarrieAnn Paukowits

The Office of Air Quality (OAQ) has reviewed an application from J & D Plating, LLC relating to the operation of a decorative chromium electroplating source.

Permitted Emission Units and Pollution Control Equipment

There are no permitted facilities operating at this source during this review process.

Unpermitted Emission Units and Pollution Control Equipment

The source also consists of the following unpermitted facilities/units:

- (a) One (1) natural gas-fired boiler, identified as B-1, constructed in August 1983, rated at 2.0 million British thermal units per hour.
- (b) One (1) natural gas-fired space heater, identified as H-1, constructed in 1983, rated at 0.1 million British thermal units per hour.
- (c) One (1) electroplating line, with a capacity of 256 pounds of steel wire per hour, including:
 - (1) one (1) decorative chromium electroplating tank, identified as DC-1, constructed in 1983, using a fume suppressant containing a wetting agent to control emissions;
 - (2) one (1) nickel electroplating tank;
 - (3) two (2) acid cleaner tanks, using sulfuric and hydrochloric acids;
 - (4) two (2) caustic cleaner tanks, using only non-VOC materials; and
 - (5) rinse tanks.

These emissions units did not previously require approval.

New Emission Units and Pollution Control Equipment

There are no new facilities proposed at this source during this review process.

Existing Approvals

The source has no previous approvals. This source has a signed Agreed Order, Case No. 2001-10754-A for NESHAP, Part 63, Subpart N compliance. The operating requirements of the Order are incorporated into this permit.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
B1	Boiler	22.0	0.67	33.33	327
H1	Heater	22.0	0.33	unknown	unknown

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the operation be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on December 27, 1999, with additional information received on July 28 and October 20, 2003.

Emission Calculations

Chromium emissions (Single HAP) from the biggest chromium electroplating source in Indiana are less than ten (10) tons per year and J & D Plating, LLC is a much smaller source in comparison. Therefore, no emission calculations were necessary for the chromium electroplating because the chromium emissions from this source will be less than ten (10) tons per year. The emissions from nickel electroplating are not calculated for the same reason.

See pages 1 and 2 of 2 of Appendix A of this document for detailed emissions calculations for the natural gas combustion units. Some acid cleaning uses hydrochloric acid in a dip process. HCl gas is a hazardous air pollutant (HAP) and may be emitted from this process. HCl gas emissions from the acid cleaning is conservatively estimated to be 1.00 tons per year. The SO₂ emissions from sulfuric acid cleaning based on AIRS Facility Subsystem Source Classification Codes and Emission Factor Listing for Criteria Air Pollutants, March 1990, SCC 3-09-011-02, are as follows:

256 lbs steel/hr x 1 ton/2,000 lbs x 0.6 lbs/ton x 8,760 hrs/yr x 1 ton/2,000 lbs = 0.336 tons SO₂ per year

J & D Plating, LLC
Elwood, Indiana
Permit Reviewer:MES

Page 4 of 11
MSOP 095-11713-00110

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source or emissions unit to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA, the department, or the appropriate local air pollution control agency.”

Pollutant	Potential To Emit (tons/year)
PM	0.017
PM ₁₀	0.070
SO ₂	0.342
VOC	0.051
CO	0.773
NO _x	0.920

HAPs	Potential To Emit (tons/year)
Chromium	less than 10
Benzene	0.00002
Dichlorobenzene	0.00001
Formaldehyde	0.00069
Hexane	0.0166
Toluene	0.00003
Lead	0.000004
Cadmium	0.00001
Manganese	0.000004
HCl	1.00
Nickel	less than 10
TOTAL	Less than 25

- (a) The existing source is subject to 326 IAC 20-8 but not subject to 326 IAC 2-5.5-1(b)(2) (registration) because the source uses hexavalent chromium for decorative coating instead of trivalent chromium and the source emits less than major source levels. Therefore, the source is subject to the provisions of 326 IAC 2-6.1-3(a).
- (b) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive emissions are not counted toward determination of PSD

and Emission Offset applicability.

Actual Emissions

No previous emission data has been received from the source.

Limited Potential to Emit

The table below summarizes the total potential to emit, reflecting all limits, of the emission units.

	Limited Potential to Emit (tons/year)						
Process/facility	PM	PM ₁₀	SO ₂	VOC	CO	NO _x	HAPs
Chromium Electroplating	-	-	-	-	-	-	< 10
Nickel Electroplating	-	-	-	-	-	-	< 10
Acid Cleaning	-	-	0.336	-	-	-	1.00
Combustion (boiler and space heater)	0.017	0.070	0.006	0.051	0.773	0.920	0.017 individual; 0.017 total
Total Emissions	0.017	0.070	0.342	0.051	0.773	0.920	< 10 individual; < 25 total

The values in the table represent the unrestricted potential to emit of each emission unit.

County Attainment Status

The source is located in Madison County.

Pollutant	Status
PM ₁₀	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Madison County has been designated as attainment or unclassifiable for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Prevention of Significant

Deterioration (PSD), 326 IAC 2-2.

- (b) Madison County has been classified as attainment or unclassifiable for all remaining criteria pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

Part 70 Permit Determination

326 IAC 2-7 (Part 70 Permit Program)

This existing source is still not subject to the Part 70 Permit requirements because the potential to emit (PTE) of:

- (a) each criteria pollutant is less than one hundred (100) tons per year,
- (b) a single hazardous air pollutant (HAP) is less than ten (10) tons per year, and
- (c) any combination of HAPs is less than twenty-five (25) tons per year.

This status has been verified by the OAQ inspector assigned to the source.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS) (326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) Tank DC-1 is subject to the National Emission Standards for Hazardous Air Pollutants, 326 IAC 20, (40 CFR 63, Subpart N, and 326 IAC 20-8-1). Pursuant to 40 CFR 63, Subpart N, and 326 IAC 20-8-1, the chromium electroplating operations are subject to the following conditions:
 - (1) The Permittee shall comply with the requirements of this condition on and after the compliance date for the tank.
 - (A) During tank operation, the Permittee shall control chromium emissions discharged to the atmosphere from tank DC-1 by:
 - (i) Not allowing the concentration of total chromium in the exhaust gas stream discharged to the atmosphere to exceed one-hundredth milligrams of total chromium per dry standard cubic meter of ventilation air (0.01 mg/dscm) [equivalent to four and four-tenths times ten raised to the power of negative six grains of total chromium per dry standard cubic foot of ventilation air (4.4×10^{-6} gr/dscf)]; or
 - (ii) Not allowing the surface tension of the electroplating bath contained within the tank to exceed forty-five dynes per centimeter (45 dynes/cm) [equivalent to three and one-tenth times ten raised to the power of negative three pound-force per foot (3.1×10^{-3} lb_f/ft)] at any time during operation of tank DC-1 when a chemical fume suppressant containing a wetting agent is used.
 - (2) The Permittee shall monitor the surface tension of the electroplating baths. Operation of tank DC-1 at a surface tension greater than 45 dynes per centimeter shall constitute

noncompliance with the standards.

- (A) The Permittee shall monitor the surface tension of the electroplating bath during tank operation according to the following schedule:
 - (i) The surface tension shall be measured once every 4 hours during operation of the tank with a stalagmometer or a tensiometer as specified in Method 306B, appendix A of this part.
 - (ii) The time between monitoring can be increased if there have been no exceedances. The surface tension shall be measured once every 4 hours of tank operation for the first 40 hours of tank operation after the compliance date. Once there are no exceedances during 40 hours of tank operation, surface tension measurement may be conducted once every 8 hours of tank operation. Once there are no exceedances during 40 hours of tank operation, surface tension measurement may be conducted once every 40 hours of tank operation on an ongoing basis, until an exceedance occurs. The minimum frequency of monitoring allowed by this subpart is once every 40 hours of tank operation.
 - (iii) Once an exceedance occurs as indicated through surface tension monitoring, the original monitoring schedule of once every 4 hours must be resumed. A subsequent decrease in frequency shall follow the schedule laid out in paragraph (B) above. For example, if a Permittee had been monitoring a tank once every 40 hours and an exceedance occurs, subsequent monitoring would take place once every 4 hours of tank operation. Once an exceedance does not occur for 40 hours of tank operation, monitoring can occur once every 8 hours of tank operation. Once an exceedance does not occur for 40 hours of tank operation on this schedule, monitoring can occur once every 40 hours of tank operation.
- (B) Once a bath solution is drained from tank DC-1 and a new solution added, the original monitoring schedule of once every 4 hours must be resumed, with a decrease in monitoring frequency allowed following the procedures in paragraphs (ii) and (iii) above.
- (3) A summary report shall be prepared to document the ongoing compliance status of the chromium electroplating operation. This report shall be completed annually, retained on site, and made available to IDEM upon request. If there are significant exceedance of chromium air emission limits (as defined in 40 CFR Part 63.347(h)(2)), then semiannual reports shall be submitted to:

Indiana Department of Environmental Management
Air Compliance Branch, Office of Air Quality
Chromium Electroplating
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206
- (4) The chromium electroplating operations shall be subject to the record keeping and reporting requirements as indicated in the chromium electroplating NESHAP.

- (c) The requirements of Section 112(j) of the Clean Air Act (40 CFR Part 63.50 through 63.56) are not applicable to this source because the source is not a major source of hazardous air pollutant (HAP) emissions (i.e., the source does not have the potential to emit 10 tons per year or greater of a single HAP or 25 tons per year or greater of a combination of HAPs) and the source does not include one or more units that belong to one or more source categories affected by the Section 112(j) MACT Hammer date of May 15, 2002.
- (d) The one (1) natural gas-fired boiler, identified as B-1, rated at 2.0 million British thermal units per hour is not subject to the New Source Performance Standards, 326 IAC 12, 40 CFR 60.40, 40 CFR 60.40a, 40 CFR 60.40b and 40 CFR 60.40c, Subparts D, Da, Db and Dc because it has a capacity less than 10 million British thermal units per hour.

State Rule Applicability - Entire Source

326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

The unrestricted criteria pollutant emissions from this source, which was constructed in 1983 and is not one (1) of the twenty-eight (28) listed source categories, are less than 250 tons per year. Therefore, the requirements of 326 IAC 2-2, PSD, are not applicable.

326 IAC 2-4.1-1 (New Source Toxics Control)

This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Clean Air Act Amendments. Therefore, the requirements of 326 IAC 2-4.1-1, New Source Toxics Control, are not applicable.

326 IAC 2-6 (Emission Reporting)

This source is located in Madison County and the potential to emit PM_{10} , NO_x , CO, VOC and SO_2 is less than one hundred (100) tons per year. Therefore, 326 IAC 2-6 does not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary alternative opacity limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 6-2 (Particulate Emission Limitations for Sources of Indirect Heating)

The one (1) boiler was constructed and in operation prior to September 21, 1983. Therefore, the boiler is subject to the requirements of 326 IAC 6-3-2. This limitation is based on the following equation is given in 326 IAC 6-2-3:

$$Pt = C \times a \times h / 76.5 \times Q^{0.75} \times N^{0.25}$$

where:

Pt = Pounds of particulate matter emitted per million British thermal units (lb/MMBtu) heat input

Q = Total source maximum operating capacity rating in million British thermal units per hour (MMBtu/hr) heat input. The maximum operating capacity rating is defined as the maximum capacity at which the facility is operated or the nameplate capacity, whichever is specified in the facility's permit application, except when some lower capacity is contained in the facility's operation permit; in which case, the capacity specified in the operation permit shall be used.

C = Maximum ground level concentration with respect to distance from the point source at the "critical" wind speed for level terrain. This shall equal 50 micrograms per cubic meter for a period not to exceed a sixty (60) minute time period.

N = Number of stacks in fuel burning operation.

a = Plume rise factor which is used to make allowance for less than theoretical plume rise. The value 0.67 shall be used for Q less than or equal to 1,000 mmBtu/hr heat input. The value 0.8 shall be used for Q greater than 1,000 mmBtu/hr heat input.

h = Stack height in feet.

For the one (1) boiler:

$$Pt = 50 \times 0.67 \times 22 / 76.5 \times (2.0)^{0.75} \times 1^{0.25} = 5.72 \text{ lb/MMBtu}$$

Pursuant to 326 IAC 6-2-3(e), for Q less than 250 million British thermal units per hour, Pt shall not exceed 0.6 pound per million British thermal units. Therefore, the one (1) boiler is limited to emissions of 0.6 pound per million British thermal units.

Based on Appendix A and AP-42, the potential PM emission rate is 1.90 pound per million cubic feet of natural gas or 0.0019 pound per million British thermal units. Therefore, the boiler will comply with this rule.

326 IAC 6-3 (Particulate Emission Limitations for Manufacturing Processes)

- (a) Pursuant to 326 IAC 6-3-1(c)(6), this rule is not applicable to the chromium electroplating operations because a particulate limit for the electroplating is established in 326 IAC 20-8-1.
- (b) All other manufacturing processes at this source have potential particulate emissions less than 0.551 pounds per hour. Therefore, pursuant to 326 IAC 6-3-1(b)(14), the requirements of 326 IAC 6-3-2 are not applicable.

326 IAC 20-1-1 (Incorporation of federal regulations)

The chromium electroplating operation, subject to 326 IAC 20-8, is required to comply with the requirements of 40 CFR 63, Subpart A, concerning general provisions for emission standards for hazardous air pollutants.

326 IAC 20-8 (Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks)

The chromium electroplating operation is required to comply with the requirements of 40 CFR 63, Subpart N, National Emission Standards for Chromium Emissions from Hard and Decorative Electroplating and Anodizing Tanks. as described in the "Federal Rule Applicability" section of this TSD.

Conclusion

The operation of this decorative chromium electroplating source shall be subject to the conditions of the attached proposed Minor Source Operating Permit 095-11713-00110.

**Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100
Small Industrial Boiler**

Page 1 of 2 TSD App A

Company Name: J & D Plating, LLC
Address City IN Zip: 2740 South P Street, Elwood, IN 46035
MSOP Number: 095-11713
Plt ID: 095-00110
Reviewer: CarrieAnn Paukowits
Date: December 27, 1999

One (1) boiler and one (1) space heater

Heat Input Capacity
MMBtu/hr

Potential Throughput
MMCF/yr

2.10

18.40

	Pollutant					
	PM*	PM10*	SO2	NOx	VOC	CO
Emission Factor in lb/MMCF	1.90	7.60	0.600	100 **see below	5.50	84.0
Potential Emission in tons/yr	0.017	0.070	0.006	0.920	0.051	0.773

*PM emission factor is filterable PM only. PM10 emission factor is filterable and condensable PM10 combined.

**Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

See page 2 for HAPs emissions calculations.

Appendix A: Emissions Calculations
Natural Gas Combustion Only
MM BTU/HR <100
Small Industrial Boiler
HAPs Emissions

Page 2 of 2 TSD App A

Company Name: J & D Plating, LLC
Address City IN Zip: 2740 South P Street, Elwood, IN 46035
MSOP Number: 095-11713
Plt ID: 095-00110
Reviewer: CarrieAnn Paukowits
Date: December 27, 1999

HAPs - Organics					
Emission Factor in lb/MMcf	Benzene 0.002	Dichlorobenzene 0.001	Formaldehyde 0.075	Hexane 1.80	Toluene 0.003
Potential Emission in tons/yr	1.93E-05	1.10E-05	6.90E-04	1.66E-02	3.13E-05

	HAPs - Metals					
Emission Factor in lb/MMcf	Lead 0.001	Cadmium 0.001	Chromium 0.001	Manganese 0.0004	Nickel 0.002	Total
Potential Emission in tons/yr	4.60E-06	1.01E-05	1.29E-05	3.50E-06	1.93E-05	0.017

Methodology is the same as page 1.

The five highest organic and metal HAPs emission factors are provided above.
 Additional HAPs emission factors are available in AP-42, Chapter 1.4.